

**FLEXIBLE MOULDING COMPOUNDS**

GRADE	BSS	SHORE A	SG	APPLICATIONS
DVF 431 103	12	95	1.32	Hard flooring tiles
UM15 030	16	93	1.31	Electrical plugs and connectors
UM16AS	16	93	1.34	Anti static flooring
CM19 033	24	87	1.33	Ca/Zn. General purpose mouldings
DVF 433 690	35	80	1.36	Non-marring, injection moulding & extrusion
UM39 040	38	78	1.39	Car mats and general purpose injection moulding
UM45 030	46	73	1.31	Easy flow suitable for the manufacture of electrical plugs
DVF 435 100	50	71	1.35	Extrusion/moulding
UM50NT	52	70	1.32	Low toxic moulding / sink plugs
DVF 436 100	60	66	1.34	Extrusion/moulding
UM65 044	62	65	1.43	General purpose injection moulding
UM63NT	64	64	1.25	Low toxic moulding
DVF 436 690	65	63	1.35	Non-marring, injection moulding & extrusion
DVF 427 230	70	61	1.23	F&DA, injection moulding and extrusion
CM83 034	75	59	1.32	Ca/Zn. General purpose soft moulding and extrusion
AV8519/2N	85	55	1.19	Oil resistant footwear, formulated to meet BS EN 344-1
DVF 438 600	85	55	1.35	Extrusion/moulding
FM105XP	104	49	0.60	Expandable shoe soles
DVF 430 690	125	43	1.31	Injection moulding

The data given above are typical results from laboratory tests. They do not form the whole or part of a specification.

Since the conditions under which our products may be used are beyond our control, recommendations are made without guarantee and customers should ensure that materials supplied are satisfactory for their requirements.

